

Part-of-speech tagging models for parsing

Rebecca Watson


Computer Laboratory
University of Cambridge

March 7, 2006

Contents

- 1 RASP
- 2 Data
- 3 Experimentation
 - Tagger Experimentation
 - Parser Experimentation
- 4 Conclusions

Assuming a PoS tagger is used as a front end to parsing...




- Should the tag ambiguity be resolved by the tagger or be passed on to the parser?
- Can a parser perform PoS tagging more accurately than a PoS tagger?
- How does the chosen PoS tagging model affect parser performance?

Example

- **Sentence Boundary Detection:** We all walked up the hill.
- **Tokenisation:** We all walked up the hill .
- **PoS Tagging**
 - First order HMM PoS tagger using CLAWS II tagset: 149 PoS tags + 13 punctuation tags.
 - Single tag-per-word (tpw) output:
We_PPIS2 all_DB2 walked_VVD up_RP the_AT hill_NN1 ...
 - Multiple tpw output (with posterior tag probabilities):
We(PPIS2:0.999983, NP1:1.73948e-05) all(DB2:0.803405, DB:0.168974, RR:0.0276206) walked(VVD:0.858121, VVN:0.141879) ...
 - Probability of a parse is the product of all shift/reduce action probabilities that resulted in creation of the parse *multiplied by the posterior tag probabilities*.
- **Lemmatiser**
We_PPIS2 all_DB2 walk+ed_VVD up_RP the_AT hill_NNL1

Parser Output

- Syntactic tree → grammatical relations (GRs)
- Evaluation scheme based on GRs.



Example

- We all walked up the hill.

(ncsubj walk+ed_VVD We_PPIS2 _)

(dobj walk+ed_VVD hill_NN1)

(det hill_NN1 the_AT)

(ncmod prt walk+ed_VVD up_RP)

- Single tpw (ncmod _ We_PPIS2 all_DB2)
- Multiple tpw (ncmod _ walk+ed_VVD all_RR)
- Parser selected correct PoS tag:

all(DB2:0.803405, DB:0.168974, RR:0.0276206)

The action probabilities out-weigh the tag probabilities.

Therefore, worth passing on tag ambiguity if parser can perform PoS tagging more accurately than a PoS tagger.

Data

- [Parc 700 Dependency Bank \(DepBank\)](#): King *et al.* (2003)
- [560 sentence subset](#) : outlined in Kaplan *et al.* (2004)
- [DepBank560](#): Briscoe and Carroll (2005) extended DepBank with gold-standard GRs and (manually corrected) PoS tags.
- [NE markup](#): for DepBank560 provided by Stephan Riezler, coauthor of Kaplan *et al.* (2004).

[Gold Standards](#): We have both gold standard PoS tags and GRs so we can contrast PoS models both in terms of tagger and parser performance.

Contents

- 1 RASP
- 2 Data
- 3 Experimentation
 - Tagger Experimentation
 - Parser Experimentation
- 4 Conclusions

Tagging Experimentation

Can a parser perform PoS tagging more accurately than a PoS tagger?

This Work

- We will compare tagging accuracy of:
 - **STAG and MTAG**: PoS tagger with single or multiple tpw output.
 - **MTAG-SYS and MTAG-SYS-DEF**: Apply system thresholds over the MTAG input.
 - **TOP-PARSE**: top ranked parse (corresponding PoS tags).
 - **NUM-TOP**: PoS tags corresponding to the highest number of parses in the parse forest.
 - **NUM-ALL**: Normalised counts of NUM-TOP rank tags.
 - **WEIGHT-TOP**: Highest scoring tag based upon the (normalised) sum of probabilities of parses in which tags occur.
 - **WEIGHT-ALL**: Scores for WEIGHT-TOP rank tags.

Evaluation

- **Standard measures:** Precision and Recall.

- **MRR:** mean reciprocal rank of tags.

$$MRR = \frac{1}{\#tags} \sum_{i=1}^{\#tags} \frac{1}{correct-tag-rank_i}$$

- **Sent:** The percentages of sentences containing at least one tagging error.

Results

- First four rows illustrate performance of the PoS tagger (also with RASP's thresholds).
- Upper bounds: provided by MTAG, errors here are caused by the unknown word module in the PoS tagger.

Tag Setup	Avg tpw [†]	Precision	Recall	MRR	Sent
STAG	1	97.23	97.23	97.18	40.71
MTAG-SYS-DEF (MSD)	1.12	88.50	98.79	97.94	21.79
MTAG-SYS (MS)	1.23	80.86	99.42	98.26	11.25
MTAG (M)	1.51	65.89	99.78	98.42	4.64
MSD-TOP-PARSE	1	95.38	95.38	95.38	59.11
MS-TOP-PARSE	1	94.47	94.47	94.41	64.46
M-TOP-PARSE	1	93.77	93.77	93.71	69.29
MSD-NUM-TOP	1	92.72	93.86	93.68	65.71
MSD-NUM-ALL	1.12	89.23	98.65	95.99	24.11
MSD-WEIGHT-TOP	1	94.67	95.84	95.66	54.82
MSD-WEIGHT-ALL	1.12	89.23	98.65	97.05	24.11

Table: Tagging Performance.[†]The average tag per word.

Results

- PoS tagger (STAG) outperforms all of the parser based PoS selection.
- Emulated performance over data with higher level of unseen words though same trends were witnessed.

Tag Setup	Avg tpw [†]	Precision	Recall	MRR	Sent
STAG	1	97.23	97.23	97.18	40.71
MTAG-SYS-DEF (MSD)	1.12	88.50	98.79	97.94	21.79
MTAG-SYS (MS)	1.23	80.86	99.42	98.26	11.25
MTAG (M)	1.51	65.89	99.78	98.42	4.64
MSD-TOP-PARSE	1	95.38	95.38	95.38	59.11
MS-TOP-PARSE	1	94.47	94.47	94.41	64.46
M-TOP-PARSE	1	93.77	93.77	93.71	69.29
MSD-NUM-TOP	1	92.72	93.86	93.68	65.71
MSD-NUM-ALL	1.12	89.23	98.65	95.99	24.11
MSD-WEIGHT-TOP	1	94.67	95.84	95.66	54.82
MSD-WEIGHT-ALL	1.12	89.23	98.65	97.05	24.11

Table: Tagging Performance.[†]The average tag per word.

Results

- Parser based models can't improve on the ranking of the PoS tagger either.

Tag Setup	Avg tpw [†]	Precision	Recall	MRR	Sent
STAG	1	97.23	97.23	97.18	40.71
MTAG-SYS-DEF (MSD)	1.12	88.50	98.79	97.94	21.79
MTAG-SYS (MS)	1.23	80.86	99.42	98.26	11.25
MTAG (M)	1.51	65.89	99.78	98.42	4.64
MSD-TOP-PARSE	1	95.38	95.38	95.38	59.11
MS-TOP-PARSE	1	94.47	94.47	94.41	64.46
M-TOP-PARSE	1	93.77	93.77	93.71	69.29
MSD-NUM-TOP	1	92.72	93.86	93.68	65.71
MSD-NUM-ALL	1.12	89.23	98.65	95.99	24.11
MSD-WEIGHT-TOP	1	94.67	95.84	95.66	54.82
MSD-WEIGHT-ALL	1.12	89.23	98.65	97.05	24.11

Table: Tagging Performance.[†]The average tag per word.

Contents

- 1 RASP
- 2 Data
- 3 Experimentation
 - Tagger Experimentation
 - Parser Experimentation
- 4 Conclusions

Parsing Experimentation

How does the chosen PoS tagging model affect parser performance (accuracy, coverage, efficiency)?

- Tagging experimentation illustrated that the parser could not perform PoS tagging as accurately (or efficiently) as the PoS tagger.
- However, tagging accuracy does not necessarily translate to equally detrimental parsing performance because the parser can recover from certain tag confusions and not others.

This Work

- Compare the parser's coverage, accuracy and efficiency given different PoS tag models.
- We will compare parser performance over several tagging models:
 - **PoS tagger:** STAG, MTAG, MTAG-SYS-DEF, MTAG-SYS.
 - **Parser tagging models:** NUM-TOP and WEIGHT-TOP (over MTAG-SYS-DEF).
- The impact of (Gold standard) PoS tagging and NE.
- Explore a hybrid (dynamic) tag selection model.

Evaluation

- **Standard measures:** Precision, Recall and F_1 (Accuracy).
- **Frag:** the proportion of sentences that result in a fragmentary parse (Coverage).
- **Time:** time taken to parse all 560 sentences (Efficiency).

Results

- Comparing PoS taggers:
 - Coverage vs. Efficiency vs. Accuracy
 - Best F_1 achieved by passing 1.12 tags per word (MTAG-SYS-DEF - tuned on Susanne).
 - Trade off between parse ambiguity and tag error rate.

Tag Setup	Prec	Rec	F_1	Frag	Time [‡]
STAG	71.06	70.96	71.01	21.25	0:03:50
MTAG-SYS-DEF	71.14	72.21	71.67	12.85	0:05:23
MTAG-SYS	70.10	71.39	70.74	10.00	0:18:27
MTAG	68.42	70.14	69.27	6.96	13:40:32
STAG-NE	73.53	69.66	71.54	25.00	0:03:13
MTAG-SYS-NE	72.54	70.49	71.50	12.68	0:10:57
MTAG-NE	71.32	69.30	70.30	9.28	0:45:51
MSD-WEIGHT-TOP	71.08	72.21	71.64	12.85	0:03:42
MSD-NUM-TOP	67.95	69.11	68.52	12.85	0:03:13
GOLD	72.94	73.12	73.03	14.46	0:04:39

Table: Parser Performance. [‡]Time as hours:minutes:seconds.

Results

- Compare performance of PoS taggers to parser based PoS tagging models:
 - PoS tagging models outperform parser based models in terms of accuracy and efficiency.

Tag Setup	Prec	Rec	F ₁	Frag	Time [‡]
STAG	71.06	70.96	71.01	21.25	0:03:50
MTAG-SYS-DEF	71.14	72.21	71.67	12.85	0:05:23
MTAG-SYS	70.10	71.39	70.74	10.00	0:18:27
MTAG	68.42	70.14	69.27	6.96	13:40:32
STAG-NE	73.53	69.66	71.54	25.00	0:03:13
MTAG-SYS-NE	72.54	70.49	71.50	12.68	0:10:57
MTAG-NE	71.32	69.30	70.30	9.28	0:45:51
MSD-WEIGHT-TOP	71.08	72.21	71.64	12.85	0:03:42
MSD-NUM-TOP	67.95	69.11	68.52	12.85	0:03:13
GOLD	72.94	73.12	73.03	14.46	0:04:39
Upper Prec	82.25	31.34	45.39	-	4:02:49
Upper Rec	17.81	87.74	29.60		

Table: Parser Performance. [‡]Time as hours:minutes:seconds.

Results

- Compare impact of gold standard NE vs. gold standard PoS tagging.
 - Gain from PoS tagging far greater than that of NE recognition
 → effort should focus on improving PoS tagger. Though this may not be the case when there are a higher number of unseen words.

Tag Setup	Prec	Rec	F ₁	Frag	Time [‡]
STAG	71.06	70.96	71.01	21.25	0:03:50
MTAG-SYS-DEF	71.14	72.21	71.67	12.85	0:05:23
MTAG-SYS	70.10	71.39	70.74	10.00	0:18:27
MTAG	68.42	70.14	69.27	6.96	13:40:32
STAG-NE	73.53	69.66	71.54	25.00	0:03:13
MTAG-SYS-NE	72.54	70.49	71.50	12.68	0:10:57
MTAG-NE	71.32	69.30	70.30	9.28	0:45:51
MSD-WEIGHT-TOP	71.08	72.21	71.64	12.85	0:03:42
MSD-NUM-TOP	67.95	69.11	68.52	12.85	0:03:13
GOLD	72.94	73.12	73.03	14.46	0:04:39
Upper Prec	82.25	31.34	45.39	-	4:02:49
Upper Rec	17.81	87.74	29.60		

Hybrid Selection

- Compare performance over non-fragmentary parses.

Tag Setup	Prec	Rec	F_1
STAG	73.66	74.94	74.30
MTAG-SYS-DEF	73.09	74.71	73.89
MTAG-SYS	72.07	73.49	72.77
MTAG	70.48	72.24	71.35
GOLD	74.58	75.70	75.14

Table: Performance over full parses.

- The increased performance illustrates that a large proportion of the errors are introduced by the frag parse output.
- The margin between STAG and GOLD has narrowed to only 0.84% F_1 suggesting that the tag errors account for a large proportion of the fragmentary parses.

Hybrid Selection

Can we rely on the grammar to find parses if and only if the correct tag sequence is input?

- Clark and Curran (2004):
 - apply a tag selection strategy where they assign a small number of supertags per word and increase the number of supertags if the parser fails to find an analysis.
 - increase efficiency, coverage and accuracy of the parser.

Hybrid Selection

- We combine the output from STAG (if full parses resulted) and MTAG-SYS-DEF (if fragmentary parses resulted for STAG).
- Increases accuracy and efficiency over MTAG-SYS-DEF (with same coverage).

Tag Setup	Prec	Rec	F ₁	Frag [†]	Time [‡]
STAG	71.06	70.96	71.01	21.25	0:03:50
MTAG-SYS-DEF	71.14	72.21	71.67	12.85	0:05:23
MTAG-SYS	70.10	71.39	70.74	10.00	0:18:27
MTAG	68.42	70.14	69.27	6.96	13:40:32
GOLD	72.94	73.12	73.03	14.46	0:04:39
HYBRID	71.59	72.39	71.99	-	-

Table: Performance over full parses.

Conclusions & Future Work

- Conclusions:

- Given a 'good' PoS tagger, parser-based tag selection models are unable to improve on the performance of the tagger or parser.
- Multiple tpw input can increase parser accuracy and coverage but at a cost to efficiency.
- Hybrid tag selection model provides a means to overcome the trade-off between tag error rates (coverage and accuracy) and increased parse ambiguity (efficiency and accuracy).

- Future Work:

- Improve integration of the posterior tag probabilities with the parser's statistical model.
- Implement a dynamic model (extension of the hybrid model).

Acknowledgements

- Ted Briscoe and John Carroll.
- Funded by: Overseas Research Student Awards (ORS) and Poyton Scholarship (Cambridge Australia Trust)

TAGGING: Previous Work

- Charniak (1996):
 - 19 PoS tags (compared to 162 in CLAWS II)
 - Parser is only slightly more accurate than the tagger (96.1% vs. 95.9%).
- Dalrymple (2004):
 - Investigated the impact of PoS tags on parse ambiguity (number of parses).
 - Suggested that selecting the tag sequence corresponding to the largest number of parses may be the correct sequence (reducing ambiguity by around 50%).

PARSER: Previous Work

- Charniak (1996):
 - Parser is only slightly more accurate than the tagger (96.1% vs. 95.9%).
 - **Parse Coverage:** increases from 99.2% to 100% using multiple-tpw.
 - **Efficiency:** Four fold increase in the computational cost.